



# SINGLE PLY SEALANT

General purpose, high quality polyurethane sealant  
for use with KEE and PVC roofing systems

## STRONGHOLD™

### PRODUCT OVERVIEW & FEATURES

StrongHold Single Ply Sealant is designed for use with KEE and PVC membranes in conjunction with terminations, drain seals and metal flashing.

StrongHold Single Ply Sealant produces a flexible joint with good adhesion to a variety of construction surfaces including sheet metal, masonry, aluminum, brick, and concrete. It exhibits excellent resistance to weather, stress, movement, water and many environmental chemicals while maintaining adhesion, cohesion, and elasticity.

Bitec supplies StrongHold Single Ply Sealant in cases of 24 standard 11 fl.oz. (.33 liter) cartridges.

### APPLICATION

StrongHold Single Ply Sealant is an easy flowing sealant, applied with an ordinary caulking gun, which skins over in a few hours and cures firm in approximately 60 hours. Surfaces to receive StrongHold Single Ply Sealant must be clean, dry, frost and grease-free.

### PHYSICAL PROPERTIES

Tensile Strength	200 psi (14 kgf/cm <sup>2</sup> )
Elongation	1000%
Shore A Hardness	33
Temperature Range	-40° to 108°F (-40° to 82°C)



# STRONGHOLD