

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Storm Breaker™ Urethane Low VOC Roof Coating

Product Code: 23200

Intended Use of the Product

For professional use only. See technical data sheet.

Name, Address, and Telephone of the Responsible Party

Manufacturer

BITEC, Inc.

#2 Industrial Park Drive

Morrilton, AR 72110

T-800-535-8597

F-501-354-3019

www.bitec.com

Emergency Telephone Number

Emergency Number: 1-800-535-8597

SECTION 2: HAZARDS IDENTIFICATION

Classification (GHS-US)

Acute Tox. 4	H332
Skin Irrit. 3	H316
Eye Irrit. 2	H319
Skin Sens. 1	H317
Resp. Sens. 1	H334
Reprod. 2	H361
STOT RE 2	H373
Aspir. 1	H304
Flam. Liq. 3	H325

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H225 Highly flammable liquid and vapor.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US) : P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
- P302+352 IF ON SKIN: Wash with plenty of soap and water.
- P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P308+313 IF exposed or concerned: Get medical advice / attention. P314 Get Medical advice / attention if you feel unwell.
- P321 Specific treatment (see information on this label). P331 Do NOT induce vomiting.
- P333+313 If skin irritation or a rash occurs: Get medical advice / attention. P337+313 If eye irritation persists: Get medical advice / attention.
- P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.
- P363 Wash contaminated clothing before reuse. P391 Collect spillage.
- P405 Store locked up.
- P501 Dispose of contents / container in accordance with local / national regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier (CAS No)	% (w/w)
Polyoxypropylene glycol	25322-69-4	25 - 50
Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3- trimethyl-	4098-71-9	10 - 25
Titanium dioxide	13463-67-7	10 - 25
Aliphatic Hydrocarbon	64742-49-0	10 - 25
HDI Homopolymer	28182-81-2	10 - 25
Xylene	1330-20-7	1.0 - 10
Ethyl Benzene	100-41-4	1.0 - 10
Fatty Acid Amide	Proprietary	1.0 - 10
Tosyl isocyanate	4083-64-1	0.10 - 1.0
Dimethyltindineodeconoate	68928-76-7	0.10 - 1.0
2-N-octyl-4-isothiazoline-3-one	26530-20-1	0.10 - 1.0

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

1,6-Hexamethylene Diisocyanate	822-06-0	0.10 - 1.0
--------------------------------	----------	------------

Composition comments Exact concentrations and chemical identities of ingredients not listed above are either classified as non-hazardous or are withheld as a trade secret as covered by OSHA's Hazard Communication Standard, 29 CFR 1910.1200(j).

SECTION 4: FIRST AID MEASURES

Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth
- First-aid measures after skin contact : Remove contaminated clothing and shoes/boots. Wash affected area with alcohol. Don't wash with water.
- First-aid measures after eye contact : Get medical attention immediately.
- First-aid measures after ingestion : If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver, and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation Harmful if inhaled. May cause allergy or asthma symptoms of breathing difficulties if inhaled.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes mild skin irritation. (Not adopted by US OSHA)

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Foam, dry chemical, CO₂, water

Special hazards arising from the substance or mixture

Hazardous decomposition: Reaction with water can create CO₂. Avoid breathing dust / fume / gas / mist / vapors / spray.

Advice for fire-fighters

Use water spray to cool non-involved containers.

Wear SCBA with full-face piece operating in a positive pressure demand mode and full protective gear.

This product is considered combustible and is a fire hazard. During a fire isocyanate vapors and other irritating gases may be generated by thermal decomposition or combustion. At temperatures above 137°F it can cause pressure build-up in closed containers. Use cold water to cool fire-exposed containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General measures : Keep upwind.

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts), concentrated (d:0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts), water (95 parts).

Add the same decontaminant to any residues and allow to stand for several days in a non-sealed container until no further reaction occurs. Once this stage is reached, close container and dispose of in accordance with the waste regulations (see section 13). Do not allow spills to enter drains or watercourses. If drains or sewers are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Avoid prolonged or repeated skin contact. Avoid breathing aerosols, spray mists, and heated vapors. Use only in well ventilated area. Use good personal and industrial hygiene practices. Keep container closed after each use.

See section 2 for further details.

Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Precautions should be taken to minimize exposure to atmospheric humidity or water as carbon dioxide may be formed which, in closed containers can result in pressurization. Care should be taken when re-opening partly used containers.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Examination of lung function should be carried out on a regular basis on persons applying this preparation.

Incompatible materials: Contact with water will cause this product to cure. Incompatible with acids, bases, and oxidizers

Recommended storage range is less than 90°F. See section 2 for further details

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits/Guidelines

CAS No.	Ingredient	Source	Value
0000100-41-4	Ethyl Benzene	OSHA	TWA 100 ppm (435 mg/m ³) STEL 125 ppm
		ACGIH	TWA: 20 ppm ^{2B} , Revised 2011,
		NIOSH	TWA 100 ppm (435 mg/m ³) ST 125 ppm (545 mg/m ³)
0000822-06-0	1,6-Hexamethylene Diisocyanate	ACGIH	TWA: 0.005 ppm Ceiling: 0.01 ppm ^S
		NIOSH	TWA 0.005 ppm (0.035 mg/m ³) C 0.020 ppm (0.140 mg/m ³) [10-minute]
0001330-20-7	Xylene	OSHA	STEL 150 ppm
		ACGIH	TWA: 100 ppm STEL: 150 ppm
0004098-71-9	Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-	ACGIH	TWA: 0.005 ppm Ceiling: 0.01 ppm ^S
		NIOSH	TWA 0.005 ppm (0.045 mg/m ³) ST 0.02 ppm (0.180 mg/m ³) [skin]

VENTILATION AND ENGINEERING CONTROLS: Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Provide adequate ventilation. This should be achieved by the use of local exhaust ventilation and good general extraction. Air-fed protective respiratory equipment must be worn by spray operators even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapor below the WEL, suitable respiratory protection must be worn. (See Personal Protection)

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Examination of lung function should be carried out on a regular basis on persons spraying this preparation.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or approved equivalent) and/or face shield. Have an eye wash station available.

HAND PROTECTION: Chemical impervious gloves required.

BODY PROTECTION: Avoid all skin contact by covering as much of the exposed skin area as possible with appropriate clothing. Wear impervious gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Viscous liquid
Odor	: Not specified
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Boiling Point	: 281 – 284 F
Flash Point	: 80 F
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not established
Relative Vapor Density at 20 °C	: Not available
Density	: 8 - 11 pounds per gallon
Solubility	: Ni, reacts with water
Partition Coefficient: N-octanol/water	: Not available
Viscosity (cSt)	: 2,000 – 40,000 cps
VOC Content	: Less than 250 g /L
% Volatile	: < 26% by volume

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Hazardous polymerization will not occur.

Chemical stability

Stable under recommended storage and handling conditions (see section 7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide may be produced.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials, amines, alcohols, and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts slowly with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing, and in extreme cases, bursting of the container.

Possibility of hazardous reactions

No data available.

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Contact with water will cause this product to cure. Incompatible with acids, bases, and oxidizers

Hazardous decomposition products

Reaction with water can create CO₂.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Based on the properties of the isocyanate content of this product, respiratory exposure may cause acute irritation and/or sensitization of the respiratory system resulting in asthmatic symptoms, wheezing and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to airborne concentrations of isocyanates well below the occupational exposure limit. Repeated exposure may lead to permanent respiratory disability.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Polyoxypropylene glycol - (25322-69-4)	2,000.00, Rat - Category: 4	No data available	No data available	No data available	No data available
Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available	20.00, Rat - Category: NA	5,000.00, Rat - Category: 4
Ethyl Benzene - (100-41-4)	3,500.00, Rat - Category: 5	15,433.00, Rabbit - Category: NA	17.20, Rat - Category: 4	No data available	4,000.00, Rat - Category: NA
2-N-octyl-4-isothiazoline-3-one - (26530-20-1)	550.00, Rat - Category: 4	690.00, Rabbit - Category: 3	No data available	0.27, Rat - Category: 2	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000100-41-4	Ethyl Benzene	IARC	Group 2b: Yes
0001330-20-7	Xylene	IARC	Group 3: Yes
0013463-67-7	Titanium dioxide	IARC	Group 2b: Yes

SECTION 12: ECOLOGICAL INFORMATION

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Toxicity

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	EC50 crustacea, mg/l	ErC50 algae, mg/l
Polyoxypropylene glycol - (25322-69-4)	650.00, Menidia beryllina	Not Available	Not Available
Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl- - (4098-71-9)	4.00, Chaetogammarus marinus	83.70, Daphnia magna	(72 hr), Scenedesmus subspicatus
Aliphatic Hydrocarbon - (64742-49-0)	Not Available	2.60, Chaetogammarus marinus	Not Available
HDI Homopolymer - (28182-81-2)	100.00, Danio rerio	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Ethyl Benzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata
2-N-octyl-4-isothiazoline-3-one - (26530-20-1)	0.0555, Oncorhynchus mykiss	0.18, Daphnia magna	0.084 (72 hr), Scenedesmus subspicatus

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

Not Measured

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Proper Shipping Name : Paint
Hazard Class : 3
Identification Number : UN 1263
Packing Group : 3

In Accordance with IMDG

Proper Shipping Name : Paint
Hazard Class : 3
Identification Number : UN 1263
Packing Group : 3

In Accordance with IATA

Proper Shipping Name : Paint

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Hazard Class : 3
Identification Number : UN 1263
Packing Group : 3

In Accordance with TDG

Proper Shipping Name : Paint
Hazard Class : 3
Identification Number : UN 1263
Packing Group : 3

SECTION 15: REGULATORY INFORMATION

Regulatory Overview \

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA)

All components of this material are either listed or exempt from listing on the TSCA Inventory.

US EPA Tier II Hazards

Fire: No

Sudden Release of Pressure: No

Reactive: No Immediate (Acute): Yes

Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

Ethyl Benzene (1,000.00)

Xylene (100.00)

EPCRA 302 Extremely Hazardous:

Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-

EPCRA 313 Toxic Chemicals:


1,6-Hexamethylene Diisocyanate Ethyl Benzene

Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl- Xylene

Proposition 65 - Carcinogens (>0.0%):

Ethyl Benzene

Titanium dioxide

 **WARNING:** This product contains, or may contain, trace quantities of substance(s) such as ethyl benzene known to the state of California to cause cancer. For more information visit www.P65warnings.ca.gov

New Jersey RTK Substances (>1%):

Ethyl Benzene

Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-

Titanium dioxide

Xylene

Pennsylvania RTK Substances (>1%):

Ethyl Benzene

Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-

Titanium dioxide

Xylene

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 01/27/2025

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

Storm Breaker Urethane Low VOC Roof Coating

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

BITEC, Inc.
#2 Industrial Park Drive
Morrilton, AR 72110
T-800-535-8597

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2019 & WHMIS