

Storm Breaker™ Silicone Skylight Coating

TECHNICAL PRODUCT INFORMATION



Storm Breaker Silicone Skylight Coating is a single component, moisture curing silicone roof coating, specially designed to provide long term protection for existing fiberglass skylights. Silicone Skylight Coating resists weathering, aging, oxidation, wind driven sand, rain, and snow, the effects of ozone, UV radiation, and the temperature extremes that are typically found on roofs.

FEATURES & BENEFITS

Storm Breaker Silicone Skylight Coating offers many benefits:

- Single part product, ready to use
- High solids content with no hydrocarbon solvents
- Can be applied in excess of 40 mils in a single coat without blistering
- Maximum adhesion to the substrate
- Clear coating permits skylights to be used and avoids safety issues from use of opaque coatings
- Moisture cure process uses moisture from the air to cure the material

PACKAGING

Storm Breaker Silicone Skylight Coating is available as a clear product, packaged in 1-gallon (120 pails / pallet) and 5-gallon pails (36 pails / pallet).

STORAGE & HANDLING

Keep containers tightly closed and in a cool, dry location. When stored unopened and in temperatures between 50°F (10°C) and 100°F (37.8°C), Silicone Skylight Coating has a recommended shelf life of 24 months from the date of manufacture.

APPLICATION

The surface to be coated must be clean, dry, and sound, as well as free of dirt, moisture, oils, algae, or other contaminants that may interfere with good adhesion. Carefully remove any loose material from the surface with a wire brush or scraper. Grease and oil should also be removed with environmentally safe solvents or an appropriate cleaner. In most cases, a high pressure water blast will be sufficient to prepare the surface. With all coatings, proper preparation is key to yielding the optimal results. BITEC always recommends adhesion testing prior to starting any roof coating jobs.

Product application should be suspended immediately and our technical service personnel contacted if the

results being obtained are less than desirable.

Storm Breaker Silicone Skylight Coating can be applied by a medium nap roller or a brush. In order to avoid sag or runoff, BITEC recommends applying at a rate of 30 mils in multiple coats. The coverage rate can vary, depending on the substrate, but should be approximately 2.25 gal / 100 ft².

PRECAUTIONS

Always protect Storm Breaker Silicone Skylight Coating from freezing temperatures. Always follow good roofing practices when deciding if the current weather conditions are conducive to a good installation. Avoid breathing vapors / mists generated by this product and always use in a well ventilated location.

Safety first! Read all label information, SDS, and precautions before using. For safety information on our products, please visit www.bitec.com.

Storm Breaker™ Silicone Skylight Coating

TECHNICAL PRODUCT INFORMATION



Technical Schedule	
Appearance	Clear
Total Solids (ASTM D-2369)	90% +/- 3%
Specific Gravity at 77°F (25°C)	1.03
Tack-Free Time	1-2 hours
Cure Time	1-4 hours
VOC	<20 g / L
Flash Point	141°F (60.6°C)

All information is given in good faith but normal tolerances of manufacture and testing will apply. BITEC reserves the right to improve and change its products at any time without prior notice or advice. The use of BITEC products is determined by local conditions and individual requirements of each contract. In consideration of the many factors involved, BITEC cannot be held responsible for the application of its products and for conditions beyond its control. All claims filed against BITEC warranties will be subject to the provisions set forth at the date of the warranty issuance, and any addendum thereto. Under no circumstances will BITEC be held liable for any damage, whether personal injury or property damage, which occur during or after the application of any BITEC products.

BITEC, Inc.
PO Box 497
#2 Industrial Park Dr
Morrilton, AR 72110
Phone: (800) 535-8597
Fax: (501) 354-3019
www.bitec.com



Copyright BITEC, Inc.
Revision Date 01/2025

BITEC®

WHEN QUALITY MATTERS™